## Tango

## **Belgotex**<sup>®</sup>



Construction	Tufted Cut Pile Carpet
Yarn	100% Stainproof Solution Dyed Nylon
Width	4.0m
Standard Roll Length	35m
Yarn Weight	800g/m² / 24oz/yd²
Total Weight	±1394g/m <sup>2</sup>
Pile Height	7.0mm
Total Thickness	9.0mm
Machine Gauge	1/8th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	< 2kV
Fire Rating	ISO 9239-1
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential / Medium Duty Commercial
Stair Rating	Suitable
Warranties	<b>15 Year Living Warranty</b> 15 Year Residential Wear Warranty 20 Year Stain Proof Warranty 20 Year Fade Proof Warranty 20 Year Colourfast Warranty 5 Year Manufacturing Defects Warranty 7 Year Commercial Wear Warranty
Environmental	Greentag Certified, GreenStar, Homestar™, Well Building Standard® Low VOC, solution dying uses no water, Eco-Wash™ Treatment, ISO 14001
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.

For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz

- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.
- B.